Altus® 40 RTS

404S2 1240260 **409R2** 1240261

Somfy DESIGNED FOR SILENCE

RTS Radio Technology Somfy®


Offers control via Radio Technology Somfy® (RTS)

Technical Features


Voltage Supply	120V AC
Index Protection Rating	Motor: IP 44 Fast Connector: IP55
Limit Switch Type	Electronic (RTS)
Limit Switch Capacity	200 Turns

Temperature Working Range	14°F to 104°F (-10°C to 40°C)
Insulation Class	Class 1 for 120V AC
Antenna	Integrated into power cord. Power cord must be at least 12 inches and must not come in contact with metal.

Dimensions



NOTE: Illustration dimensions in millimeters (mm).



2 mounting holes for self tapping screws. Dia. 4 mm (cat #100405B) Depth 9 mm spaced 1.14" (29 mm) apart.

Self tapping mounting screws are included with each motor.

	404S2	409R2
L1	20.08 in. (510 mm)	20.87 in. (530 mm)
L2	19.13 in. (486 mm)	19.92 in. (506 mm)
L3	20.59 in. (523 mm)	21.38 in. (543 mm)
Cable Length	1.6 ft (.5 m) to Fast Connector	

Certifications

c UL us

Specifications

	404S2	409R2
Torque	4 Nm	9 Nm
Nominal Voltage	120V / 60Hz	
Rated Current	.95A	1.05A
Speed	36 rpm	18 rpm
Thermal Protection	5 minutes	
Radio Frequency	433.42 MHz	
***Sound Level**	57 dBA	54 dBA

Sound level:
*According to standards ISO 3741 NF 31022 in dBA ref 1pW at nominal torque without end product.

Fabrication recommendations:

- Operational noise level is reduced when motor, tube, and mechanical accessories are properly adapted to motorized applications.
- Free plays have to be minimized between the accessories and the end product tube to ensure quiet performance of the motor.
- Interior Tube Diameter (ID) > or = 38mm must be respected to prevent contact with the basic motor tube.
- 400 Series Drive Stop and Screw (9147894) is recommended to prevent noise and drive wheel separation from motor shaft.

Type of power cable

RTS
120V AC / 60Hz
3-Conductor 1.6 ft. SJTW Cable on Motor with Fast Connector




Extension Cable (sold separately)



3 Conductor Fast Connector Extension Cable with NEMA Plug (RTS & RS485)

9021113	1.4 ft.	9021114	4.4 ft.
9021115	8.4 ft.	9020791	10.4 ft.
9020792	18 ft.	9020793	24 ft.



3 Conductor Fast Connector Extension Cable with Open Leads or No NEMA
9021157 8.4 ft.



3 Conductor Panel Mount Female Fast Connector for direct connection to J-Box
9026398 Panel Mount Female Fast Connector

somfy®

© Somfy Systems, Inc. • **AUGUST 2025**

www.somfypro.com