



LT50/60
Mechanical Accessories

Motor Brackets

Dimensions (mm)	Cat. Number	Description
	6070284	LT50 Angle Plate with Elongated Holes Allowing Adjustment - Zinc plated steel - Compatible with idler end bearing support Cat. No. 9080239 and intermediate bearing support Cat. No. 6050438 - Maximum motor torque - 50 Nm - Maximum system load - 69 Kg. (152 Lbs.) - Replaces SOMFY Cat. No. 6070283
	6070446	LT50/60 Motor Bracket with 1/2" Conduit Connector - Four mounting holes provided - Lateral space requirement for installation: 28 mm - Zinc plated steel - Must be used with either spring ring Cat. No. 4350026, or locking spring ring Cat. No. 4350027 (not included) - Maximum motor torque - 85 Nm or 100 Nm when locking spring ring Cat. #4350027 is used.
 Spring ring needs to be replaced with locking spring ring Cat. #4350027 to obtain maximum torque and load capability	6070499 6070501 6070502	Universal Bracket with Spring Ring - Assembled to accept Inch Series threaded screws 1/4 - 20, 5/16 - 18 (nuts molded into bracket) Universal Bracket with Spring Ring - Zamak Material - 2 holes for M6 hex or 1/4 - 20 flat head screw on 48 mm diameter - 2 holes for M8 hex screw on 60 mm diameter - 2 countersunk holes for M8 screw on 60 mm diameter - Lateral space requirement for installation: 27 mm - Maximum motor torque - 85 Nm or 100 Nm when used with locking spring ring Cat. No. 4350027, and 5/16 - 18 or M8 bolts without molded nuts - Maximum system load - 200 Kg. (441 Lbs.) when used with locking spring ring Cat. #4350027 With M8 and M6 nuts molded in bracket - Same as above - Maximum system load 200 Kg. (441 Lbs.)
	6070500	Weld-on Bracket Without Spring Ring - Steel bracket without surface treatment - For welding to mounting plates of all kinds. Lateral space requirement for installation: 23 mm + thickness of mounting plate - Must be used with spring ring Cat. No. 4350026 or locking spring ring Cat. No. 4350027 (not included) - Maximum motor torque - 85 Nm or 100 Nm depending on spring ring and quality of weld - Maximum system load - 200 Kg. (441 Lbs.) when used with locking spring ring Cat. #4350027