# CMO Mechanical Accessories

| Dimensions (mm) | Cat. Number | Description |
|---|---|---|
|  | 6250702 | CMO Motor Bracket<br>- Converts a CMO motor head to be compatible with standard LT brackets<br>- Allows the motor to be rotated in 60° increments<br>- Delivered with two motor mounting screws<br>- Black composite<br>- Maximum motor torque - 80 Nm<br>- Maximum system load - See note below |
|  | 6250710<br><br>6250711<br><br>6250713 | CMO Awning Eye with 2.36" (60 mm) Long 7 mm Hex Shaft<br><br>CMO Awning Eye with 6.5" (165 mm) Long 7 mm Hex Shaft<br><br>CMO Awning Eye with 4" (100 mm) Long 7 mm Hex Shaft |
|  | 6250712<br><br><br><br><br><br>4100122<br>4000104 | LT CMO Awning Eye Compatible with Geiger Crank Handles<br>- Length of the shaft is (100 mm) 4"<br>- Stainless steel pin for eyepiece mounting to 7 mm Hex shaft<br>- Stainless steel stop washer & socket head screw (also sold separately)<br>- Zinc plated steel shaft<br><br>- Stainless steel lock washer<br>- Stainless steel M4 socket head screw |
|  | 6250715<br><br><br><br>6250716 | CMO Extension Shafts<br>- 7 mm Hex, 8.66" (220 mm) long<br>- Zinc plated steel<br><br>- 7 mm Hex, 13" (330 mm) long<br>- Zinc plated steel |
|  | 6250717<br><br><br>6250718<br><br>6250719 | Connecting Sleeves<br>- 7 mm Hex to diameter 11.3 mm<br>- Zinc plated steel<br>- 7 mm Hex to 8 mm Square<br>- Zinc plated steel<br>- 7 mm Hex to 7 mm Hex<br>- Zinc plated steel |
|  | 6250720 | CMO Extension Shaft with Universal Joint<br>- Shaft 7 mm Hex, 12.4" (315 mm) long - zinc plated steel<br>- Output of the universal joint is a 12 mm diameter hole<br>- Universal joint<br>- White powder coated steel<br>- Color: white fixing plate<br>- 60° outlet |

Note: Maximum system load will vary depending on application. SOMFY recommends testing of component in actual application to determine its suitability.