CMO Cables and Mechanical Accessories

Dimensions (mm)	Cat. Number	Description
	6020510	Standard LT CMO Motor Cable - 6 ft.
	6020511	Standard LT CMO Motor Cable - 12 ft.
	6020512	Standard LT CMO Motor Cable - 24 ft.
	6020515	Standard LT CMO Motor Cable - 6 ft. Long with Waterproof Plug
	6020550	LT RTS CMO Motor Cable - 6 ft.
	6020551	LT RTS CMO Motor Cable - 12 ft.
	6020554	LT RTS CMO Motor Cable - 18 ft.
	6020552	LT RTS CMO Motor Cable - 24 ft.
	6020557	LT RTS CMO Cable with 5-15P Right Angle NEMA Plug - 6 ft.
	6020558	LT RTS CMO Cable with 5-15P Right Angle NEMA Plug - 12 ft.
	6020560	LT RTS CMO Cable with 5-15P Right Angle NEMA Plug - 18 ft.
	6020559	LT RTS CMO Cable with 5-15P Right Angle NEMA Plug - 24 ft.
	6110500	Standard LT and LT CMO Motor Mounting Plate - Allows for different orientation of the LT CMO motor head in 15° increments - Zinc plated steel - Maximum motor torque - 100 Nm - Maximum system load - See note below
	6110501	CMO 100 x 100 mm LT Motor Mounting Bracket - Fits most shutter end caps - Allows for easy replacement of the BMOM/BMO motor utilizing existing mounting holes - Zinc plated steel - Maximum motor torque - 100 Nm - Maximum system load - See note below
	6250500	LT50 Manual Override Differential - The input of the differential accepts the LT50 motor shaft - The differential's output shaft can be adapted to any tube profile using the LT50 drive wheels - Maximum motor torque 40 Nm. Gain ratio 1:4 - Maximum system load - See note below
	6250505	LT50 Differential Torque Tube Connectors - For square link bars (16 x 1 mm) - Zinc plated steel
	6250506	- For round link bars (Dia. 16 x 1 mm)

Note: Maximum system load will vary depending on application. SOMFY recommends testing of component in actual application to determine its suitability.